

DT-BT1

Battery of Integrated Mount Tester



- It is specially designed for the Integrated Mount Tester.

Series Overview

The Battery for Integrated Mount Tester has a stable battery life, ensuring the Integrated Mount Tester operates reliably.

Technical Specification

Function	
Battery Type	Lithium battery
Nominal Capacity	22.2 Wh
Nominal Voltage	7.4 V
Standard Charge Current	600 mA
Recommended Charging Voltage	8.4 V
Standard Discharge Current	600 mA
Max. Discharge Current	4500 mA

Structure

Appearance Color	Gray
Product Dimensions	70 mm × 85 mm × 11 mm (2.76" × 3.35" × 0.43") (L × W × H)
Packaging Dimensions	110 mm × 100 mm × 35 mm (4.33" × 3.94" × 1.38") (L × W × H)
Net Weight	0.13 kg (0.29 lb)
Gross Weight	0.15 kg (0.33 lb)

Environment

Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)

Certifications

Certifications	ROHS
----------------	------

Ordering Information

Type	Model	Description
Battery	DT-BT1	Battery of Integrated Mount Tester

Dimensions (mm[inch])

