



4K POC Balun


SINGLE CHANNEL

Attention

1. Network cable conductor is made of copper, and it shall conform to international CAT5E or CAT6 electrical performance standard.
2. Adjust saturation of DVR, so image transmission distance will be farther.
3. In case of no image or unrecognizable image, please adjust saturation of DVR.
4. Do not use the product outdoors, because it is non-waterproof.
5. Do not connect the power supply to avoid the passive transmitter being burnt!



Wiring



Specifications

Properties

Video Transmission Distance	HDCVI_Non-POC Camera—720P:MAX.350M;1080P:MAX.250M;4MP/4K:Max.180m; HDTVI_Non-POC Camera—720P/1080P:MAX.250M;5MP/4K180M; AHD_Non-POC Camera—720P:MAX.350M;1080P:MAX.250M;5MP/4K:Max.180m; HDCVI/TVI/AHD_POC Camera—720P: MAX.150M;1080P:MAX.150M; 4MP/5MP: Max.150m;4K:MAX.80m
Compatible Format	HDCVI/AHD/TVI/CVBS
Resolution	720P/1080P/4M/5M/6M/4K
Category Type	UTP CAT5E/6 (material: CU)

Protection

ESD	1a contact discharge electricity level 3, 1b air discharge electricity level 3, Per: IEC61000-4-2
-----	---

Physical Properties

Dimension(L*W*H)	155mm×21mm×20mm
Shell	ABS
Net Weight	20.5g

Stability

MTBF	>10000H
------	---------

Environmental

Operating Temperature	-10℃~+55℃(14 °F~131°F)
Storage Temperature	-20℃~+70℃(4 °F~158°F)
Humidity	0~95%(non-condensing)



This device complies with part 15 of the FCC Rule.
Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and
(2) this device must accept any interference received,
including interference that may cause undesired operation.



MADE IN CHINA