

Titus

A PURETECH Brand

6-in-1 8K Camera Tester with 7" Touchscreen

CODE: TEST-7-6IN1-HS



Specifications

Display	7" IPS touch screen, 1280*800 resolution
CVBS	<p>1 channel BNC input & 1 channel BNC looped output;</p> <p>NTSC/PAL (Auto adapt); PTZ control; RS485 control;</p> <p>Baud 600-115200bps, compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc.;</p> <p>CVBS loop test - Send and receive colour bar generator signals and check BNC cables</p>
IP Camera Test 8K / H.265 / H.264	<p>IP Discovery / Quick ONVIF / IPC test / RTSP play / Client APK;</p> <p>Rapid Video - Auto-view videos and create testing reports</p>
IP & CVBS Test	<p>IP & CVBS are tested at the same time;</p> <p>Converter test from analogue to digital with a dual test window</p>
Coaxial HD Test	<p>8MP TVI camera test, 3840 x 2160P 15 FPS, UTC control / call OSD menu</p> <p>8MP CVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control / call OSD menu</p> <p>8MP AHD test, 3840 x 2160P 15 FPS, UTC control / call OSD menu</p> <p>HD SDI / EX-SDI2.0 camera test</p>
HDMI Input *	1 channel HDMI input; supports 1080P
Zoom Image	4x zoom to enlarge image
Capture & Playback	Screen snapshot, record, save, view and record and playback
Colour Bar Generator	<p>Output one channel PAL/NTSC;</p> <p>Colour bar video signal is for testing monitors or video cables</p>
PoE Power Output	48V PoE power output, max power 24W
DC12V Power	DC12V /3A power output
DC24V/2A Power	DC24V /2A power output
UTP Cable Test	Connection status is displayed on screen

6-in-1 8K Camera Tester with 7" Touchscreen

CODE: TEST-7-6IN1-HS

RJ45 Cable TDR Test	Test cable pair status, length, attenuation, reflectivity, impedance, skew etc; Measurement range is 180m.
Tester Play	Screen projection: tester, mobile phone and PC display at the same time (Current support is for Android mobile devices only)
Network Test	Trace route, monitor link, DHCP server, port flashing, ping test
Wi-Fi	Built in
Audio Test	1 channel audio signal input to test whether sound works as normal; 1 channel audio signal, to connect headphones
Data Monitor	Captures and analyses the command data from a controlling device; It can also send hexadecimal values.
PoE Test	Measures a POE switch or PSE power supply's voltage and cable connection status
Drop-Down Menu	Select PoE power switch, IP setting, CVBS, LAN info, HDMI IN functions etc. in any interface
External Power Supply	DC 12V 2A
Battery	Built-in 7.6V Lithium polymer battery, 7800mAh
Rechargeable	Works for around 16 hours after 3.5-4 hours charging
Operation Setting	OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc
Auto Off	1-30 (mins)
Working Temperature	-10°C ~ +50°C
Working Humidity	30% ~ 90%
Dimensions	240mm x 154mm x 46mm
Weight	620g