

WEBCAM-4MP

4MP LIVE-STREAMING USB WEBCAM

SECYOUR™



- Supports 2K / 1080p video output
- DRC digital WDR, 2D DNR
- Mic pickup range is 6 meters
- Video output: YUV / MJPEG
- Plug and play, driver free
- 1.8m USB 2.0 cable
- DC 5V

Specification	WEBCAM-4MP
Image Sensor	1/3 4MP Sensor
Video Resolution	MAX2560(H)*1440(V)
Frame Rate	1080P@30fps/4MP@30fps
Encoding Format	YUV/MJPEG
Image Effective Range	≥0.3m
Lens	Fixed
Angle of View	85°
Minimum Illumination	≤5LUX
Gain/Gain Control	Auto
White Balance	Auto
Exposure Control	Auto
Microphone Form	Built-in noise reduction microphone
Pickup Distance	6m
Sound Track	Single Sound Track
S/N	39dB
Audio Encoding Format	PCM
Audio Bit Rate	128kbps
Types	USB Integration Camera (Data and Power integration)
Data Interface	Micro USB2.0 interface
System Requirements	Windows® 10 or later, Windows 8, Windows 7, Works in USB Video Device Class (UVC) mode with supported applications: macOS 10.10 or higher/Chrome OS™/Android™ v 5.0 or higher
Indicator Light	Working: Light on. No working: light off
Power Supply	USB power supply (DC5V)
Power Consumption	<1W
Operating Temperature	-10°C~50°C
Working Humidity	<90%RH (non-condensing)
Weight	≈170g
Installation Method	Design with clip-on base to put camera on different monitor
Continuous Working Hours	More than 24 hours
Status Light	Working: Light on. No working: light off
Line Length	1.8m
Certification	CE; FCC; ROHS
Accessories	Camera blindfold, User manual