

DHI-LM65-S400

65" UHD LED Monitor



Features :

- Industrial level LCD panel, suitable for continuous 24/7 operation
- 4K Ultra-HD resolution
- Using tamper-proof metal housing
- 8ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° extra-wide viewing angle for overall viewing performance
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption
- Support multiple signals, such as VGA, HDMI, Audio ,USB multimedia, RS-232, OPS

Technical Specification

Model

Model	DHI-LM65-S400
-------	---------------

Display

Screen Size	64.5"
Aspect Ratio	16:9
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance	400cd/㎡
Contrast Ratio	1200:1
Display Color	1.07B(10bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	8ms
Refresh Rate	60Hz

Signals

Input	VGA(D-Sub)×1, HDMI×1, USB multimedia×1, Audio in×1, RS-232×1, OPS×1	
Output	RS-232×1, Audio out×1	
	Speaker	8W×2

General

Power Supply	AC100~240V(±10%), 50/60 Hz, 3.5A
--------------	----------------------------------

Consumption (Standard)	170W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	28.5kg (62.8lb)	
Gross Weight	40kg (88.2lb)	
Bezel Width	23.1mm (U/L/R/B)	
VESA	600×400mm (23.6"×15.7")	
Dimension without base (W×H×D)	1476.7×851.7×79.8mm (58.1"×33.5"×3.1")	
Package(W×H×D)	1660mm×1045mm×245mm (65.4"×41.1"×9.6")	
Work Environment	Temperature	0°C~40°C (32°F~104°F)
	Humidity	20%~85%

Accessory

Standard	HDMI cable, Power cable, Remote control, Hanging bracket
Optional	Pedestal

Certifications

Certifications	CE/FCC
----------------	--------

Dimensions(mm)

