

# DH-SD6C3425XB-HNR-A-PV1

4MP 25x Starlight IR WizSense Network PTZ Camera



**Wiz Sense**

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Powerful 25x optical zoom
- Starlight technology
- IR distance up to 150m
- Perimeter protection
- Face detection
- Metadata
- Full-color illuminator; red and blue warning light
- IP66



Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive AI solutions for industry verticals.

## System Overview

Dahua PTZ WizMind network camera adopts advanced CNN deep learning algorithms to support face recognition with high accuracy. This camera possess wide monitor range, PFA algorithm that can always present a clear, focused image while zooming, and smart wiper technology that supported by RainSensor.

## Functions

### Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005 Lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

### Smart Capture

Supports human face, human body, motor vehicle and non-motor vehicle image capture. It also supports optimization, taking snapshots and generating optimal snapshot reports.

### Face Detection

6 attributes and 8 expressions: Gender, age, glasses, expressions (anger, sadness, disgust, fear, surprise, calm, happiness and confusion), mask, beard. Face cutout setting: Face, single inch photo. Three snapshot methods: Real-time snapshot, priority snapshot, and quality priority.

### PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

### Sound and Light Alarm

The camera supports sound and light alarm. When the alarm is triggered, the camera links sound alarm and red and blue light warning, to realize the deterrence and effective intervention. It also supports customized voice importing.

**Technical Specification**

**Camera**

Image Sensor	1/2.8" CMOS
Pixel	4 MP
Max. Resolution	2560 (H) × 1440 (V)
Electronic Shutter Speed	1/1 s–1/30,000 s
ROM	4 GB
RAM	1 GB
Min. Illumination	Color: 0.005 lux@F1.6 B/W: 0.0005 lux@F1.6 0 lux (IR light on)
Illumination Distance	150 m (492.13 ft) (IR) 50 m (164.04 ft) (white light) 50 m (164.04 ft) (red and blue light)
Illuminator Number	2 (IR light) 2 (dual light fusion) 1 (red light) 1 (blue light)

**Lens**

Focal Length	4.8 mm–120 mm			
Max. Aperture	F1.6–F3.5			
Field of View	H: 55.8°–2.9°; V: 31.6°–1.6°; D: 63.7°–3.3°			
Optical Zoom	25×			
Focus Control	Auto; semi-auto; manual			
Close Focus Distance	0.8 m–5.0 m (2.62 ft–16.40 ft)			
Iris Control	Auto; manual			
DORI Distance	Detect	Observe	Recognize	Identify
	1,655 m (5429.79 ft)	653 m (2142.39 ft)	331 m (1085.96 ft)	165 m (541.34 ft)

**PTZ**

Pan/Tilt Range	Pan: 0° to 360° endless Tilt: –20° to +90°, auto flip 180°
Manual Control Speed	Pan: 0.1°–160°/s; Tilt: 0.1°–60°/s"
Preset Speed	Pan: 240°/s; Tilt: 150°/s
Preset	300
Tour	8 (up to 32 presets per tour)
Pattern	5
Scan	5
Power-off Memory	Yes
Idle Motion	Preset; Tour; Pattern; Scanning
Protocol	DH-SD Pelco-P/D (auto recognition)

**Intelligence**

Video Metadata	Motor vehicle, non-motor vehicle, face, human body detection; optimization; capturing pictures; uploading high-quality face snapshots
----------------	---

IVS (Perimeter Protection)	Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linkage tracking
Face Detection	Yes
SMD	Yes
Auto Tracking	Yes

**Video**

Video Compression	Smart H.265+; H.265; Smart H.264+; H.264B; H.264H; MJPEG
Streaming Capability	3 streams
Resolution	4M (2560 × 1440); 3M (2048 × 1536); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576); CIF (352 × 288)
Video Frame Rate	Main stream: 4M/3M/1080p/1.3M/720p (1–50/60 fps) Sub stream 1: D1/CIF (1–25/30 fps) Sub stream 2: 1080p/1.3M/720p (1–25/30 fps)
Bit Rate Control	CBR/VBR
Video Bit Rate	Default resolution of the main stream: H264: 2816–8192 kbps H265: 1024–7936 kbps
Day/Night	Auto (ICR); Color; B/W
BLC	Yes
WDR	Yes
HLC	Yes
White Balance	Auto; manual; tracking; indoor; outdoor; outdoor auto; sodium lamp; sodium lamp auto
Gain Control	Auto; manual
Noise Reduction	2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Image Stabilization	Optical
Defog	Electric
Digital Zoom	16×
Privacy Masking	Up to 24 areas can be set, with up to 8 areas in the same view; supports multiple colors and mosaic blocks
S/N Ratio	≥55dB
<b>Audio</b>	
Audio Compression	G.711a; G.711Mu; G.726; G722.1; G.729; MPEG2-Layer2; G723; PCM
<b>Network</b>	
Network Port	RJ-45 (10/100 Base-T)
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; SSL; Qos; FTP; UPnP; ICMP; SNMP; SNMPv1/v2c/v3(MIB-2); IGMP; ARP; RTCP; RTP; PPPoE; IP Filter; RTMP; Bonjour; TCP; SMB; NFS
User/Host	20 (total bandwidth: 64 MB)
Interoperability	ONVIF Profile S&G&T
Storage	FTP; Micro SD card (256 GB); NAS

Browser	IE7 and later versions Chrome 42 and earlier versions Firefox 52 and earlier versions Safari
Management Software	Smart PSS; DSS; DMSS; Easy4ip; IVSS; player; configtool; NVR; Smart Player
Mobile Client	IOS; Android; iPhone; iPad; Windows Phone

**Certifications**

Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014
----------------	--

**Port**

Audio Input	1 (LINE IN; bare wire)
Audio Output	1 (LINE OUT; bare wire)
Two-way Audio	Yes
Alarm Input	2-ch, digital input (0-5 VDC)
Alarm Output	1-ch
Alarm Linkage	Capture; preset; tour; pattern; recording; alarm digital input; send email
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection

**Power**

Power Supply	24 VDC/2.5 A ± 25% (included) PoE+ (802.3at)
Power Consumption	Basic: 13 W Max.: 23 W (illuminator+red and blue warning light+speaker+PTZ working)

**Environment**

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Operating Humidity	≤95%
Protection	IP66, TVS 6000V lightning proof; surge protection; voltage transient protection

**Structure**

Casing	ADC12
Product Dimensions	325.3 mm × Ø202.0 mm (12.81" × Ø7.95") (H × D)
Net Weight	4.6 kg (10.14 lb)
Gross Weight	9.1 kg (20.06 lb)

**Ordering Information**

Type	Part Number	Description
<b>4M WizMind PTZ Camera</b>	DH-SD6C3425XB-HNR-A-PV1	4MP 25x Starlight IR PTZ AI Network Camera
	SD6C3425XB-HNR-A-PV1	4MP 25x Starlight IR PTZ AI Network Camera
<b>Accessories</b>	DC 24V/2.5A	Power Adapter
	PFB303W	Wall Mount Bracket
	PFA114	Mount Adapter
	PFB300C	Ceiling Mount Bracket
	PFB301C	Ceiling Mount Bracket
	PFB303S	Parapet mount Bracket
	PFB301S-E	Plane mount Bracket
	PFA151	Corner mount Bracket
	PFA150	Pole Mount Bracket

**Accessories**

**Included:**



DC12V/2.5 A Power Adapter



PFA114 Wall Mount Bracket

**Optional:**



PFB303W Wall Mount Bracket



PFB300C Ceiling Mount Bracket



PFB301C Ceiling Mount Bracket



PFB303S Parapet Mount Bracket











PFB301S-E Plane mount Bracket



PFA151  
Corner Mount  
Bracket



PFA150  
Pole Mount  
Bracket

<p>Wall Mount</p> <p>PFA114+PFB303W+PFA120</p> 	<p>Ceiling Mount</p> <p>PFA114+PFB300C</p> 	<p>Ceiling Mount</p> <p>PFA114+PFB301C</p> 
<p>Pole Mount(VERTICAL)</p> <p>PFA114+PFB303W+PFA150</p> 	<p>Corner Mount</p> <p>PFA114+PFB303W+PFA151</p> 	<p>Pole Mount(HORIZONTAL)</p> <p>PFA114+PFB300C+PFA150</p> 
<p>Plane Mount</p> <p>PFA114+PFB301S-E</p> 	<p>Parapet Mount</p> <p>PFA114+PFB303S</p> 	

**Dimensions (mm[inch])**

