

PASSIVE 1CH 4K VIDEO BALUN FOR CVI/TVI/AHD (PoC Support)



CODE: TD-TT-POC-4K



Video Properties			HD-CVI / HD-TVI / AHD			
Transmission Signal			1-Channel			
Stability			>10,000h			
Transmission Distance	PoC Camera	HD-CVI	720P, 1080P, 4MP & 5MP: 150m			4K: 100m
		HD-TVI	720P, 1080P, 4MP & 5MP: 150m			4K: 100m
		AHD	720P, 1080P, 4MP & 5MP: 150m			4K: 100m
	Non PoC Camera	HD-CVI	720P: 400m	1080P: 250m	4MP: 200m	4K: 180m
		HD-TVI	720P, 1080P & 4MP: 250m			4K: 180m
		AHD	720P: 350m	1080P & 4MP: 200m		4K: 180m
Coaxial Video Connector			BNC-M			
Resolution			4K / 5MP / 4MP / 3MP / 1080P / 720P			
Suggested Cable Type			CAT5/5E/6 (UTP)			
Anti-Interference			>60dB			
ESD Protection			1a Contact Discharge Electricity Level 3; 1b Air Discharge Electricity Level 3; Per: IEC61000-4-2			
Coaxial Cable Protection			2Kv (Common Code), Per: IEC1000-4-5			

PASSIVE 1CH 4K VIDEO BALUN FOR CVI/TVI/AHD (PoC Support)



CODE: TD-TT-POC-4K

UTP Cable Protection	2Kv (Differential Code); 2Kv (Common Code), Per: IEC1000-4-5
BNC Male Impedance	75Ω
UTP Cable Impedance	100Ω
Material	Black ABS
Storage Temperature	−20°C to +70°C (−4°F to +158°F)
Working Temperature	-10°C to +55°C (14°F to +131°F)
Working Humidity	Less than 95% (RH)