

## 200m2 Wall-Mounting Phase-Array Hearing Loop Amplifier

Part No. PDA5/DW



## **Overview**

- A new wall-mounting 2 x 3.25A phase-array hearing loop amplifier ideal for use in areas up to 200m2.
- Intuitive LED interface allows simple set-up of input levels, output current, phantom power and metal compensation.
- 1 XLR mic input, 1 XLR line input and 1 outreach connector.
- Anti-tamper lock function.
- Class D output stage for maximum efficiency.
- Superior audio processing and powerful CPU provide life-like speech and first class music reproduction.
- Fault relay & LED indicators provide clear indication of operation and fault status.
- Industry leading dual action automatic gain control compensates for poor microphone technique.
- Line level output for recording or daisy-chaining multiple units to cover larger areas.

## **More Information**

## **Technical Specifications**

Type Wall-mounting (requires a permanent 5A fused spur connection to Mains).

Coverage 200m2 approx. 230V 50Hz. Mains supply



T 01942 322744

E sales@c-tec.co.uk



















2 x 3.25A loop drive current @ 1 Ohm; Loop output volage 14V. Output

Max battery size and type

1 x XLR mic input with switchable 12V phantom power, 1 x XLR line input, 1 x Outreach connector and 1 x Auxiliary inputs

Optical TOS Link connector.

VU Meter (shows the amplitude of the audio); HOT! (lit if the output stage is getting hot); FAULT1 / Indicators

FAULT2 (lit if loop 1 or loop 2 has shut down because of overheating or excessive current; POWER Controls Line Input, Microphone, 12V Phantom, Outreach, Metal Comp, Loop Drive 1, Loop Drive 2, Phase Shift. Mic (3-way pluggable); Line In (3-way connectors); Loop (4 way connector); Outreach (4-way pluggable Connections

connector); Line Out (3-way pluggable connector); Fault Relay (3-way pluggable connector); 230Va

Product dimensions (mm) 298 (H) x 308 (W) x 74 (D) mm.

Mild steel zintec, 1mm thick, black powder coated. Construction & finish

IP40. IP Rating Weight 3.35kg

Operating conditions/temperature  $-5^{\circ}$ C to  $+40^{\circ}$ C. Max relative humidity: 95%.















