



QVIS® | 2MP COVERT IP CAMERA

KEY FEATURES

- 3.7mm Pinhole Lens
- Brackets Included
- Size: 78(W) x 104(H) x 25.8(D)mm
- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- WDR Starlight
- Main Stream: 1080P@30fps
- 3MP HD Lens
- Support Micro SD Card, Max. 512G
- Audio I/O, Alarm I/O.
- 1x RS485
- With Internal POE

COVERT-IP-2MP	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H) x 1097(V)
Compression	H.264 / H.264+ / H.265 / H.265+ / JPEG / AVI
TV System	PAL / NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000 Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.005Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Supported
LENS	
Focus Length	3.7mm Pinhole Lens / 82°(F2.8) with 2M cable
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
NETWORK	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Supported QR Code
PoE	Internal, Supported IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2304 x 1296@20fps
Main Stream 2	1920 x 1080@30fps
Main Stream 3	1280 x 720@30fps
Sub Stream 1	720 x 480@20fps 720 x 480@30fps
Tri Stream	352 x 288@20fps 352 x 288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari (lower than version 12)
Smart Phone	iPhone, iPad, Android, Android Pad



QVIS® | 2MP COVERT IP CAMERA

KEY FEATURES

- 3.7mm Pinhole Lens
- Brackets Included
- Size: 78(W) x 104(H) x 25.8(D)mm
- 1/2.8" SONY Starvis
Back-illuminated CMOS Sensor
- WDR Starlight
- Main Stream: 1080P@30fps
- 3MP HD Lens
- Support Micro SD Card,
Max. 512G
- Audio I/O, Alarm I/O.
- 1x RS485
- With Internal POE

CAMERA FEATURES

Day / Night	Colour / B&W
Image Config	Saturation / Brightness / Contrast / Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control), Video Tampering
Corridor Pattern / Defog Mode / ROI / BLC / Motion Detection	Supported
WDR	WDR: 96dB
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / CMS / Web / SD card
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese

INTERFACE

Audio	2-Way Audio
Alarm	1ch Alarm In/1ch Alarm Out
SD Card Slot	Support Max 512GB
RS485	Support

GENERAL

Housing	Metal
Anti-cut Bracket	YES
IR Cut Filter	NO
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension (mm)	78(W) x 104(H) x 25.8(D)
Weight	766.2g