

5MP

DUAL-ILLUMINATION HD ANALOGUE TURRET CAMERA

Titus

CODE: TD-5COL-IL-TUR-FG



WHITE LIGHT
& IR



HD
ANALOGUE
INPUT



20m
LED
RANGE



IP67
INGRESS
PROTECTION



AUDIO
BUILT-IN
MIC



Camera

Image Sensor	5MP CMOS
Image Resolution	5MP (2880 x 1620)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s to 1/100,000s; NTSC: 1/30s to 1/100,000s
Minimum Illumination	0.05 lux @ F1.6 (Colour, 30 IRE); 0.005 lux @ F1.6 (Black / White, 30 IRE); 0 lux (Illuminator On)
S/N Ratio	>65dB
Illumination Distance	20m (65.62 ft.)
Illuminator On / Off Control	Auto / Manual
Illuminator Number	1 (Warm White Light); 1 (IR Light)
Pan / Tilt / Rotation Range	Pan: 0°-360°; Tilt: 0°-78°; Rotation: 0°-360°

5MP

DUAL-ILLUMINATION HD ANALOGUE TURRET CAMERA



CODE: TD-5COL-IL-TUR-FG

Lens Information

Lens Type	Fixed Focal			
Lens Mount	M12			
Focal Length	2.8mm			
Maximum Aperture	F1.6			
Field of View	Horizontal: 106°; Vertical: 56°; Diagonal: 125°			
Iris Control	Fixed			
Close Focus Distance	0.8m (2.62 ft.)			
DORI Distance	Detect	Observe	Recognise	Identify
	56m (183.73 ft.)	22.4m (73.49 ft.)	11.2m (36.75 ft.)	5.6m (18.37 ft.)

Video

Video Frame Rate	CVI: PAL: 5MP @ 25fps; 4MP @ 25fps; 1080P @ 25fps NTSC: 5MP @ 25fps; 4MP @ 30fps; 1080P @ 30fps
	AHD: PAL: 4MP @ 25fps; NTSC: 4MP @ 30fps
	TVI: PAL: 4MP @ 25fps; NTSC: 4MP @ 30fps
	CVBS: PAL: 960H; NTSC: 960H
Resolution	5MP (2880 x 1620); 4MP (2560 x 1440); 1080P / 2MP (1920 x 1080); 960H (960 x 576 / 960 x 480)
Day / Night	Auto (ICR); Colour / Black / White
BLC	BLC / HLC / WDR
WDR	DWDR
White Balance	Auto; Area White Balance

5MP

DUAL-ILLUMINATION HD ANALOGUE TURRET CAMERA

Titus

CODE: TD-5COL-IL-TUR-FG

Video

Gain Control	Auto; Manual
Noise Reduction	2D NR
Illumination Modes	Smart IR & White Light; White Light Mode; IR Mode
Mirror	Supported
Privacy Masking	Supported (8 Areas)

Certification

Certifications	<ul style="list-style-type: none">- CE-LVD: EN62368-1- CE-EMC: EN55032; EN55035- FCC: 47 CFR FCC Part 15, Subpart B- UL/CUL: UL62368-1 & CAN/CSA C22.2 No. 62368-1-14
----------------	--

Ports

Video Output	CVI; TVI; AHD; CVBS Outputs by 1x BNC
Audio Input	1 Channel Built-In Mic (-A)

Parameters & Dimensions

Power Supply	12VDC \pm 30%
Power Consumption	Up to 3.1W (12VDC; Warm Light On)
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Working Temperature	-40°C to +60°C (-40°F to +140°F)
Working Humidity	Less than 95% (RH)
Protection	IP67
Casing	Metal
Product Dimensions	85.7mm x Φ 94mm (3.37" x Φ 3.7")
Net Weight	310g (0.68lb)
Gross Weight	430g (0.95lb)