



PTZ Network Keyboard with Joystick Control & 3" TFT Screen

CODE: VIP-IPKEYBOARD-S2

NDA
Compliant



Control up to
256 PTZs



Intuitive
Joystick Control



Seamless NVMS
Integration



RS232 &
Network Control



Control & Display

Operation Interface	4D Joystick, Knob & Keypad
Display	TFT LCD Screen (320 x 240)



Network Parameters

Interface	1x RJ45 10/100Mbps Adaptive Ethernet Port
Control Mode	PTZ Mode; Platform Mode & Serial Port Mode
Network Management	Upgrade via NVMS 2.1 Client



Serial Port Parameters

Serial Port Interfaces	RS422 x1; RS232 x1
Baud Rate	1200bps, 2400bps, 4800bps, 9600bps & 19200bps



Other Parameters & Dimensions

Power Supply	DC12V 2A
PoE	IEEE802.3 af
Power Consumption	< 5W
Operating Environment	Temperature: -10°C to +55°C; Humidity: 20% to 80% (non-condensing)
Storage Environment	Temperature: -10°C to +60°C; Humidity: Less than 90% (non-condensing)
Dimensions	321mm x 179.2mm x 108.5mm
Weight	1.63kg
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)