

PASSIVE 4K VIDEO BALUN FOR CVI/TVI/AHD (Twin Pack)



CODE: TD-TT-4K-105A



Video Properties		HD-CVI / HD-TVI / AHD		
Transmission Signal		1-Channel		
Stability		>10,000h		
Transmission Distance	HD-CVI	720P: 400m	1080P: 250m	4MP & 4K: 200m
	HD-TVI	720P & 1080P: 250m	4MP: 200m	5MP & 4K: 180m
	AHD	720P: 300m	1080P & 4MP: 200m	5MP & 4K: 180m
Coaxial Video Connector		BNC-M		
Twisted-Pair Video Connector		Screw Interface		
Resolution		4K / 5MP / 4MP / 3MP / 1080P / 720P		
Suggested Cable Type		CAT5/5E/6 (UTP)		
Anti-Interference		>60dB		
ESD Protection		1a Contact Discharge Electricity Level 3; 1b Air Discharge Electricity Level 3; Per: IEC61000-4-2		
Coaxial Cable Protection		2Kv (Common Code), Per: IEC1000-4-5		
UTP Cable Protection		2Kv (Differential Code); 2Kv (Common Code), Per: IEC1000-4-5		
BNC Male Impedance		75Ω		
UTP Cable Impedance		100Ω		
Material		Black ABS		

PASSIVE 4K VIDEO BALUN FOR CVI/TVI/AHD (Twin Pack)



CODE: TD-TT-4K-105A

Storage Temperature	–20°C to +70°C (–4°F to +158°F)
Working Temperature	-10°C to +55°C (14°F to +131°F)
Working Humidity	Less than 95% (RH)