



Dual-Illumination Fixed Lens Turret Camera

CODE: TURVIPS4-4KIL-FG

IP

8^{4K}
MP

NDA
Compliant



People
Detection



Built-In
Microphone



White Light
& IR



Dual Stream
Support

Camera

Image Sensor	1/2.7" CMOS
Video Compression	H.265+ / H.265 / H.264+ / H.264
Resolution	8MP, 6MP, 4MP, 2K, 2MP (1 to 20fps)
Electronic Shutter	1/3s to 1/100,000s
Minimum Illumination	0.01 lux at F1.6 (AGC on); 0 lux with IR
Light Range	IR Range: 30m White Light Range: 30m
Lens	2.8mm
Field of View	Horizontal: 106.5° Vertical: 58.5° Diagonal: 124°
Focus	Fixed
Image Correction	BLC, HLC, WDR, Digital NR
S/N Ratio	≥50dB
Detect	77m (253ft.)
Observe	31m (101ft.)
Recognise	15m (51ft.)
Identify	8m (25ft.)

Interfaces

Network	RJ45 (10/100 Base-T)
Audio	1CH audio input; 1CH built-in microphone
Storage	Micro SD card slot (supports up to 256GB)
Reset Button	Yes

Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Web Browser	Google Chrome; Microsoft Edge; Firefox; Safari
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 6 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, DDNS, 802.1x, HTTP, P2P, QoS
Interface Protocol	ONVIF



Dual-Illumination Fixed Lens Turret Camera

CODE: TURVIPS4-4KIL-FG

IP

8^{4K}
MP




Functions (continued)

Alarm Events	Video Motion Detection, Video Exception, SD Card Error, SD Card Full
AI Events	Line Crossing Detection, Region Intrusion Detection (People)
Additional Functions	Watermark, Video Mask, Heartbeat, Corridor Mode, Image Distortion Correction, ANR
Security	HTTPs Encryption, Configuration Encryption, Illegal Login Lock, IP Address Filtering, 802.1x Authentication, Basic and Digest Authentication for HTTP



Compatible Accessories



Cable Management Ring

CODE: VIP-RING-03-GR



Wall Bracket

CODE: VIP-WALL-BK0203-G



Parameters & Dimensions

Power Supply	DC12V / PoE
PoE	IEEE802.3af
Power Consumption	< 6.8W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Storage Environment	Temperature: -30°C to +65°C; Humidity: Less than 95% (non-condensing)
Dimensions	Ø94.6mm x 82.8mm
Weight	0.45kg
Installation	Ceiling or wall mounted
Protection Grade	IP67
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)