



Case B (175)

Casing for secure wired connection of Ajax devices.



- 3 GRADE
EN 50131
- EN 60670-1
- PD 6662 2017
- INCERT




Safe and quick connection with compatible devices

Install Ajax devices using Case. Choose the casing size with the required slot number depending on the number of products to be installed. Run cables and secure the devices in the simplest way. Quick and reliable fastening using durable latches and non-falling screws.



This is a two-slot casing. There are alternative-sized casings available for different device combinations.



Easy installation and maintenance

- Pre-installed tamper to detect the lid opening and alert of detachment of the casing from the surface
- Mounting holes placed at different angles and pre-installed spirit level to set the casing horizontally
- Perforated zones and fasteners for easy cable routing and management
- Multiple use – even after dismantling and changing device configuration
- Lid and device fixing in two positions – errors are excluded
- All mountings are included – PRO does not need to take an additional mount to the facility

Compliance	Compatibility	Installation	Technical specifications	Complete set
EN 50131 (Grade 3) EN 60670-1:2005 PD 6662:2017 INCERT	Case B (175) is a two-slot casing. Compatible devices Superior LineSplit Fibra Superior LineProtect Fibra Superior MultiRelay Fibra Superior MultiTransmitter IO (4X4) Fibra	Operating temperature range from –10°C to +40°C Operating humidity up to 75%	Color white, black Dimensions 175 × 225 × 57 mm Weight 414 g	Case B (175) Installation kit Quick start guide



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/case-fibra/

- ✉ support@ajax.systems
- 📍 @AjaxSystemsSupport_Bot
- 🌐 ajax.systems