

Case D (430)

Casing for up to eight Ajax modules and two 18 Ah batteries



Safe and quick connection with compatible devices

Install Ajax devices using Case. Choose the casing size with the required slot number depending on the number of products to be installed. Run cables and secure the devices in the simplest way. Quick and reliable fastening using durable latches and non-falling screws.



This is a case for installing one of the many possible device configurations. Due to the modular installation system, Case D (430) can house up to eight devices simultaneously. Compatible devices include Superior MultiTransmitter Fibra (without casing), Superior Hub Hybrid (4G) (without casing), Superior LineSplit Fibra, Superior LineProtect Fibra, Superior MultiRelay Fibra, Superior LineSupply (45 W) Fibra, Superior LineSupply (75 W) Fibra, and 7–18 A·h batteries. There are alternative-sized casings available for different device combinations.



Easy installation and maintenance

- Pre-installed tamper to detect the lid opening and alert of detachment of the casing from the surface
- Mounting holes placed at different angles and pre-installed spirit level to set the casing horizontally
- Perforated zones and fasteners for easy cable routing and management
- Multiple use – even after dismantling and changing device configuration
- The flexible system with modules and holders provides thousands of mounting configurations to suit any setup
- All mountings are included – PRO does not need to take an additional mount to the facility

Module Holder (type A) is used to install Superior LineSplit Fibra, Superior LineProtect Fibra, and Superior MultiRelay Fibra modules. **Module Holder (type B)** is used to install Superior MultiTransmitter Fibra (without casing) and Superior Hub Hybrid (4G) (without casing). No holders needed for Superior LineSupply (45 W) / (75 W) Fibra; these devices are installed on casing rails.

There are four Module Holder (type A) in the complete set. Additional holders and Module Holder (type B) are sold separately.

Compatibility

Case D (430) is a casing for installing one of the many possible device configurations. This case can house up to eight devices simultaneously.

Compatible devices

- Superior Hub Hybrid (4G) (without casing)
- Superior MultiTransmitter Fibra (without casing)
- Superior LineSplit Fibra
- Superior LineProtect Fibra
- Superior MultiRelay Fibra
- Superior MultiTransmitter IO (4X4) Fibra
- Superior LineSupply (45 W) Fibra
- Superior LineSupply (75 W) Fibra
- 7–18 A·h batteries (not included in the set)

Compliance

EN 50131 (Grade 3)
EN 60670-1:2005
PD 6662:2017
INCERT

Technical specifications

Color

white, black

Dimensions

430 × 400 × 133 mm

Weight

3,381 g
white Case D (430)
3,343 g
black Case D (430)

Installation

Operating temperature range
from –10°C to +40°C

Operating humidity
up to 75%

Complete set

- Case D (430)
- Tamper board
- Holding stripe for a battery
- Module Holder (type A) – 4 pcs.
- Installation kit
- Quick start guide



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/case-fibra/

- ✉ support@ajax.systems
- 📍 @AjaxSystemsSupport_Bot
- 🌐 ajax.systems