


DomeCam HLVF

Wired AI-powered security IP camera with a 2.8–12 mm motorized varifocal lens, hybrid illumination, True WDR, audio and alarm inputs/outputs, microphone, and PoE/12 V. For outdoor and indoor use.



Product versions



DomeCam HLVF (5 Mp)
 up to 2880 × 1620 px (3K UHD)



DomeCam HLVF (8 Mp)
 up to 3840 × 2160 px (4K UHD)

Adaptability by design

DomeCam HLVF is engineered to adapt to any scenario. Featuring a motorized varifocal lens with autofocus, a single camera can provide both wide coverage and sharp detail. This flexibility simplifies installation, enables smarter setups, and ensures consistently clear visuals.

Adjustable focal length for wide or focused views: 2.8–12 mm

Instant autofocus for sharp visuals after adjustment

Seeing in color after dark

Thanks to hybrid illumination, DomeCam HLVF records in full color even at night. Once motion or an object is detected, the camera automatically switches from infrared (IR) to white light to capture every detail. The sudden flash of white light also acts as a deterrent, stopping intruders in their tracks.

IR illumination range: up to 40 m (130 ft)

White light illumination range: up to 25 m (80 ft)

Seamless user experience

- AI-powered object recognition: people, vehicles, and pets
- High-resolution visual verification of alarms via video scenarios
- Built-in microphone with noise suspension and echo cancellation
- Instant transition from notifications to on-site video recordings
- Camera synchronization with security system modes
- Sirens or automation devices activation upon detection¹
- Real-time monitoring with a customizable video wall
- True WDR (Wide Dynamic Range) for better image quality

Smooth archive navigation

- Proprietary JetSparrow technology for instant, secure video streaming and smooth archive navigation
- Instant access to live view
- Fast archive navigation using event timeline, calendar view, and search filters
- Dual streams for instant preview and optimized bandwidth usage
- Quick video clip export in just a few clicks


Uncompromising security and privacy

- Passwordless camera authentication via mutual TLS (mTLS) handshake
- TLS-encrypted video streams
- User-controlled access to video content
- Secure video export with digital signature verification
- Multi-tiered account protection: passcodes, biometrics, and two-factor authentication
- Session control for additional account security
- NDAA-compliant components

Easy installation and maintenance

- Adding to an Ajax system via QR code
- Remote control and configuration via Ajax apps
- Support for ONVIF/RTSP authorization²
- Alarm and audio inputs and outputs to connect third-party devices
- Motion detection zone configurations via mobile and desktop Ajax apps
- Real-time system health monitoring with automatic state checks

Flexible video surveillance for any scale and scenario





DomeCam HLVF cameras can operate without an Ajax NVR. In this case, video footage is stored locally on a microSD card if one is installed.

Compliance with standards	Video and optics		Key features
CE RoHS NDAA	Resolution		Motorized varifocal lens
	5 MP version: up to 2880 × 1620 px @ 25 fps (3K UHD)	8 MP version: up to 3840 × 2160 px @ 25 fps (4K UHD)	Allows changing the viewing angle from wide to narrow
	Lens focal length 2.8–12.0 mm		JetSparrow
	Field of view horizontal: 31°–111° vertical: 17°–57° diagonal: 35°–135°		Proprietary Ajax protocol for fast and secure video transmission
	Image processing True WDR (hardware and software)	Video stream ONVIF ¹ RTSP	Motion detection Built-in software to detect motion in the frame
	Bitrate 100 Mbps, full-duplex	Video compression H.265, H.264	Object recognition with built-in AI People Pets Vehicles
	Illumination	Simultaneous live view Up to 5 channels	Alarm verification Motion detection AI-powered recognition Detector alarm Automation scenarios
	IR illumination range: up to 40 m (130 ft)	White light illumination range: up to 25 m (80 ft)	Built-in digital microphone

Power supply Power supply unit 8–14 V== Ethernet 10/100 Mbps (RJ-45) Ethernet port PoE standard 802.3at/af Power consumption up to 12 W	Installation Operating temperature range from –40 °C to +60 °C from –40 °F to 140 °F Operating humidity up to 90%	Enclosure Color black, white Dimensions 136 × 136 × 115.3 mm 5.35" × 5.35" × 4.53" Weight 430 g 15 oz Protection class IP67 IK10	Complete set DomeCam HLVF Installation template Installation kit Quick start guide
--	---	--	---

¹ To activate sirens or automation devices upon detection, the system must include such devices and an Ajax hub.
² Full support for Profile S, partial support for Profiles T and M.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/domecam-hlvf

-  support@ajax.systems
-  @AjaxSystemsSupport_Bot
-  ajax.systems