

# EAGLE-5COL-BUL-FW

## 5MP STARLIGHT HDCVI BULLET



- Full-Colour starlight
- 20 m LED distance
- Max. 20fps@5MP
- CVI/CVBS/AHD/TVI switchable
- Audio in interface, built-in mic (-A)
- 2.8 mm fixed lens
- IP67, 12V±30% DC



### System Overview

Experience 5MP full HD colour video and the simplicity of reusing existing coaxial infrastructure with HDCVI. The full-colour starlight HDCVI camera presents a high quality colour image with rich details even in total darkness. It offers various fixed lens models with a multi-language OSD and HD/SD switchable output. It adopts two powerful warm white LED illuminators, covering an effective range up to 20 m (65.61 ft). The LEDs switch on automatically in darkness to capture detail-packed full-colour images 24/7, ensuring effective identification of objects. It is an ideal choice for applications such as schools, retail centers and parking lots.

### Functions

#### Full-Colour Starlight

The camera adopts F1.2 large aperture lens and a 1/2.7" high performance sensor. With higher amount of absorbed light and advanced image processing algorithm, the camera presents an impressive lowlight performance with an exceptional balance between noise reduction and the blur of moving object.

#### Warm Supplemental lights

With one warm supplemental LED lights, the camera is able to provide a colourful and vivid image even in total dark. By default, the camera is set to smart light mode, in which the camera can automatically adjust the exposure time and light sensitivity simultaneously to avoid overexposure of the objects in the image center. Also, the sensitivity and intensity of the LED lights can be remotely controlled by the OSD menu.

#### Broadcast-quality Audio\*

Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.

\*This function is available for select models.

#### 4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm.

\*Audio input is available for some models of HDCVI cameras.

#### Long Distance Transmission

HDCVI technology guarantees long-distance and real-time transmission without any loss. It supports up to 700 m for 5MP HD video via coaxial cable, and up to 300 m via UTP cable.\*

#### Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

#### Multiple-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

#### Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 rating, making it suitable for indoor or outdoor environments. With a working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

## Technical Specification

### Camera

|                                   |  |
|-----------------------------------|--|
| Image Sensor                      | 1/2.7 inch CMOS                                    |
| Effective Pixels                  | 2592 (H) × 1944 (V), 5MP                           |
| Scanning System                   | Progressive  |
| Electronic Shutter Speed          | PAL: 1/25s–1/100000s<br>NTSC: 1/30s–1/100000s      |
| S/N Ratio                         | >65dB  |
| Minimum Illumination              | 0.005Lux/F1.2, 0Lux White Light on                 |
| Fill Light (White Light) Distance | Distance up to 20 m (65.61 ft)                     |
| Fill Light On/Off Control         | Auto; manual                                       |
| Fill Light Number                 | 1  |
| Pan/Tilt/Rotation Range           | Pan: 0°–360°<br>Tilt: 0°–180°<br>Rotation: 0°–360° |

### Lens

|                      |  |                      |                      |                     |                    |
|----------------------|--|----------------------|----------------------|---------------------|--------------------|
| Lens Type            | Fixed-focal  |                      |                      |                     |                    |
| Mount Type           | M12  |                      |                      |                     |                    |
| Focal Length         | 2.8mm  |                      |                      |                     |                    |
| Max. Aperture        | F1.2   |                      |                      |                     |                    |
| Field of View        | 2.8 mm: 111° × 83° × 56°<br>(diagonal × horizontal × vertical) |                      |                      |                     |                    |
| Iris Type            | Fixed iris   |                      |                      |                     |                    |
| Close Focus Distance | 2.8 mm: 2.1 m (6.89 ft)  |                      |                      |                     |                    |
| DORI Distance        | Lens   | Detect               | Observe              | Recognize           | Identify           |
|                      | 3.6 mm   | 80.0 m<br>(262.5 ft) | 32.0 m<br>(105.0 ft) | 16.0 m<br>(52.5 ft) | 8.0 m<br>(26.2 ft) |

### Video

|                 |   |
|-----------------|---|
| Frame Rate      | CVI:<br>PAL: 5M@20fps, 4M@25fps, 1080P@25fps;<br>NTSC: 5M@20fps, 4M@30fps, 1080P@30fps<br>AHD:<br>PAL: 5M@20fps, 4M@25fps;<br>NTSC: 5M@20fps, 4M@30fps<br>TVI:<br>PAL: 5M@20fps, 4M@25fps;<br>NTSC: 5M@20fps, 4M@30fps<br>CVBS:<br>PAL: 960H;<br>NTSC: 960H |
| Resolution      | 5M (2592 × 1944); 4M (2560 × 1440); 1080P (1920 × 1080); 960H (704 × 576/704 × 480);  |
| BLC             | BLC/HLC/WDR   |
| WDR             | DWDR  |
| White Balance   | Auto; manual  |
| Gain Control    | Auto; manual  |
| Noise Reduction | 2D NR   |
| Smart Light     | Yes   |
| Mirror          | Off/On  |

|                 |                            |
|-----------------|----------------------------|
| Privacy Masking | Off/On (8 area, rectangle) |
|-----------------|----------------------------|

### Certifications

|                |  |
|----------------|--|
| Certifications | CE (EN55032, EN55024, EN50130-4, EN60950-1)<br>FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)<br>UL (UL60950-1+CAN/CSA C22.2 No.60950-1) |
|----------------|--|

### Port

|              |  |
|--------------|--|
| Video Output | Video output choices of CVI/TVI/AHD/CVBS by one BNC port |
|--------------|--|

### Audio Interface

|             |  |
|-------------|--|
| Audio Input | One channel of built-in mic (only for audio model) |
|-------------|--|

### Power

|                   |                                   |
|-------------------|-----------------------------------|
| Power Supply      | 12V ±30% DC                       |
| Power Consumption | Max 3.0W (12V DC, White Light on) |

### Environment

|                       |  |
|-----------------------|--|
| Operating Temperature | -40°C to +60°C (-40°F to 140°F); <95% (non-condensation) |
| Storage Temperature   | -40°C to +60°C (-40°F to 140°F); <95% (non-condensation) |
| Protection Grade      | IP67   |

### Structure

|                   |  |
|-------------------|--|
| Casing            | Metal throughout the whole casing                    |
| Camera Dimensions | 174.5 mm × 70.6 mm × 72.3 mm (6.87" × 2.78" × 2.85") |
| Net Weight        | 0.33 Kg (0.73 lb)                                    |
| Gross Weight      | 0.44 Kg (0.97 lb)                                    |

### Dimensions (mm[inch])

