



G5 Bullet Spec Sheet

| UVC-G5-BULLET

Next-gen indoor/outdoor 2K HD PoE Camera.

- 2K (4MP) video resolution
- Flexible 3-axis adjust mount
- 9 m (30 ft) IR night vision
- AI event detections
- Record audio with an integrated microphone
- Connect and power using PoE
- Weatherproof (outdoor exposed)

Mechanical

Dimensions	Without mount: Ø75.5 x 74.4 mm With mount: Ø75.5 x 150 mm
Weight	Without mount: 225g With mount: 315g
Enclosure material	Polycarbonate, aluminium alloy
Mount material	Wall mount: Aluminium alloy, polycarbonate Pole mount: aluminium alloy
Weatherproofing	IPX4
Resistance	IK04

Optics

Sensor	5MP CMOS
Lens	Fixed focal length
View angle	H: 84.4°, V: 45.4°, D:99.8°
Night mode	Built-in IR LED illumination and IR cut filter

Video

Resolution	4MP 2688 x 1512 (16:9)
Max. frame rate	30FPS
Image settings	Colour, brightness, sharpness, contrast, white balance, exposure control, "DNR, 3DNR, NR by motion, masking, text overlay sharpness, saturation, noise

System

Processor	Dual-core Arm® Cortex®-A7 based chip
Network Interface	10/100 MbE RJ45 port
Max. power consumption	4W
Power method	PoE
Supported voltage range	37-57V DC
Button	Factory reset
Mounting	Wall, pole mount
Ambient operating temperature	-20 to 40°C
Ambient operating humidity	0 to 90% noncondensing
Certifications	FCC, IC, CE

Audio

Microphone	Yes (Can be disabled)
------------	-----------------------

Software

Web application	UniFi Protect: Version 2.2.7 or 2.7.28 and later
Mobile app	UniFi Protect IOS™ and Android™: Version 1.10.0 and later