



Dual-Illumination Fixed Lens Turret Camera

CODE: TURVIPS4-6IL-FG

IP

6MP

NDA
Compliant



People
Detection



Built-In
Microphone



White Light
& IR



Dual Stream
Support

Camera

Image Sensor	1/2.7" CMOS
Video Compression	H.265+ / H.265 / H.264+ / H.264
Resolution	6MP (1 to 20fps), 4MP (1 to 25fps), 2MP (1 to 25fps)
Electronic Shutter	1/2s to 1/100,000s
Minimum Illumination	0.007 lux at F1.6 (AGC on); 0 lux with IR
Light Range	IR Range: 30m White Light Range: 20m
Lens	2.8mm
Field of View	Horizontal: 110.5° Vertical: 57° Diagonal: 131°
Focus	Fixed
Day & Night	ICR
Image Correction	BLC, HLC, WDR, Digital NR
S/N Ratio	≥50dB
Detect	60m (196ft.)
Observe	24m (78ft.)
Recognise	12m (39ft.)
Identify	6m (20ft.)

Interfaces

Network	RJ45
Audio	1CH built-in microphone

Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Web Browser	IE (plug-in required); Google Chrome; Microsoft Edge; Firefox; Safari
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 3 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, 802.1x, HTTP
Interface Protocol	ONVIF
Smart Events	Line Crossing Detection, Region Intrusion Detection (People Only)



Dual-Illumination Fixed Lens Turret Camera

CODE: TURVIPS4-6IL-FG

IP

6MP


Functions (continued)

Additional Functions	Watermark, Video Mask, Heartbeat
Security	Video Encryption, Firmware Encryption, Configuration Encryption, Illegal Login Lock, IP Address Filtering, 802.1x Authentication, Basic and Digest Authentication for HTTP

Parameters & Dimensions

Power Supply	DC12V / PoE
PoE	IEEE802.3af
Power Consumption	< 6W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Storage Environment	Temperature: -30°C to +65°C; Humidity: Less than 95% (non-condensing)
Dimensions	Ø94.6mm x 82.8mm
Weight	0.423kg
Installation	Ceiling or wall mounted
Protection Grade	IP67
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)

Compatible Accessories



Cable Management Ring
CODE: VIP-RING-03-GR



Wall Bracket
CODE: VIP-WALL-BK0203-G