

# DH-XVR5104HS-I3

4CH Penta-brid 5MP Value/1080P Compact 1U 1HDD WizSense Digital Video Recorder



WizSense

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

## Series Overview

Dahua Technology, a world-leading video-centric smart IoT solution and service provider, debuted its new XVR series, XVR5000-I3 Series featuring max.full-channel SMD Plus to benefit customers from AI upgrade (The number of channels differs depending on the model. Please refer to the specifications below for information on the number of channels.). This series has been developed to reduce false-alarm rates and the cost of human surveillance, thus bringing great value to customers in search of products with accurate human/vehicle alarm to raise the security level of various indoor and outdoor facilities.

## Functions

### Face Recognition

Dahua Face Recognition technology extracts the features of captured faces and compares them with that in face database.

\*Face Recognition takes effect when Face is selected in AI Mode.

### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.

\*Perimeter Protection takes effect when IVS&SMD is selected in AI Mode.

\* *The information below only applies to hardware version 3.0. of the product.*

- 1-channel QuickPick 2.0 for analog channels which improves target retrieval efficiency.
- 4-channel SMD Plus for analog channels or 6-channel SMD by camera which allows the device to trigger accurate alarms for humans and vehicles.
- 4-channel perimeter protection for analog channels which supports tripwire and intrusion detection powered by AI.
- 1-channel face recognition for analog channels which supports face comparison.
- 4-channel AI Coding saves on storage and bandwidth while maintaining the details of targets in videos.
- Supports HDCVI, AHD, TVI, CVBS and IP video input.
- Supports up to 6-channel IP camera input and each channel can be up to 6 MP. The incoming bandwidth reaches 32 Mbps.
- Smart H.265+ and H.265 dual-stream video compression.
- IoT and POS capabilities.



### SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

\*SMD Plus takes effect when SMD or IVS&SMD is selected in AI Mode.

### QuickPick 2.0

By employing the back-end perimeter protection algorithm, QuickPick 2.0 not only retains the capability to identify the color of clothing and vehicles, which was offered by its predecessor QuickPick 1.0, but it also possesses the enhanced ability to detect various types of hats, clothing and vehicles, thus greatly improving the accuracy of the search function.

\*QuickPick 2.0 takes effect when Quick Pick is enabled in AI Mode.

### Irregular Black Block Masking

Dahua's black block masking function supports the use of irregular shapes for masking, ensuring privacy in public and private locations.

## Technical Specification

### System

Main Processor	Industrial-grade processor
Operating System	Embedded Linux
Operating Interface	Web; Local GUI

### QuickPick 2.0

QuickPick 2.0 AI by Recorder (Number of Channels)	1 channel
---	-----------

### Perimeter Protection

Perimeter Performance AI by Recorder (Number of Channels)	Advanced Mode: 2 channels, 10 IVS rules for each channel General Mode: 4 channels, 10 IVS rules for each channel
---	---

### Face Detection

Face Attributes	6 attributes
Face Detection Performance of AI by Recorder (Number of Channels)	1 channel (up to 8 face images/s each channel)

### Face Recognition

Face Database Capacity	Up to 10 face databases with 10,000 images.
Face Recognition Performance of AI by Recorder (Number of Channels)	1 channel

### SMD Plus

SMD Plus by Recorder	4 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and lighting condition change
SMD Plus by Camera	6 channels

### AI Video Quality Analytics

AI Video Quality Analytics by Recorder	4 channels: Supports detecting brightness levels, color cast, defocus, overexposure, contrast levels, black and white
--	---

### Scene Changing

Scene Changing by Recorder	1 channel
----------------------------	-----------

### Irregular Black Block Masking

Irregular Black Block Masking by Recorder	1 channel
---	-----------

### Audio and Video

Analog Camera Input	4 BNC ports, supports HDCVI/AHD/TVI/CVBS auto-detect
Camera Input	1. CVI: 5 MP@25 fps; 5 MP@20 fps; 5 MP@10/12.5 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@50/60 fps; 720p@25/30fps. 2. TVI: 5 MP(2560 x 1944)@20 fps; 5 MP(2960 x 1665)@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps.

	3. AHD: 5 MP@20 fps; 4 MP@25/30 fps; 1080p@25/30 fps; 720p@25/30 fps.
IP Camera Input	Up to 6 channels of IPC access 2 IP channels by default +4 channels (analog channels are converted to IP channels) incoming bandwidth: 32 Mbps, recording bandwidth: 32 Mbps and outgoing bandwidth: 32 Mbps *After IP extension is enabled, Video Quality Analytics, Scene Changing, Face Recognition, Face Detection, SMD, Perimeter Protection and QuickPick 2.0 cannot be used.
Encoding Capacity	Encode Enhancement disabled : Main stream: Channels 1-2 5M-N@(1 fps-25 fps), others 5M-N@(1 fps-12 fps); Channels 1-2 4M-N/1080p@(1 fps-30 fps), others 4M-N/1080p@(1 fps-15 fps); 1080N/720p/960H/D1/CIF@(1 fps-30 fps); Sub stream: D1/CIF@(1 fps-15 fps); Encode Enhancement enabled : Main stream: 4-ch 5M-N@(1 fps-25 fps);(4 channels can be transformed to 5MP@6 fps) 4-ch 4M-N/1080p@(1 fps-25 fps); 1080N/720p/960H/D1/CIF@(1 fps-30 fps); Sub stream: D1/CIF@(1 fps-15 fps); *When Encode Enhancement is enabled, Video Quality Analytics, Scene Changing, Face Recognition, Face Detection, Perimeter Protection and QuickPick 2.0 cannot be used.
Dual-stream	Yes
Video Bit Rate	32 kbps-6144 kbps
Audio Sampling	8 kHz, 16 bit
Audio Bit Rate	64 kbps
Video Output	1 HDMI, 1 VGA HDMI: 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
Multi-screen Display	When IP extension mode not enabled: 1/4 When IP extension mode enabled: 1/4/6
Third-party Camera Access	Panasonic; Sony; Hanwha; Axis; Arecont; ONVIF

### Compression Standard

Video Compression	AI Coding; Smart H.265+; H.265; Smart H.264+; H.264
Audio Compression	G.711a; G.711u; PCM

### Network

Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.)
Mobile Phone Access	iOS; Android
Interoperability	ONVIF 24.06 (Profile T; Profile S; Profile G); CGI; SDK
Browser	Chrome; IE; Safari; Edge; Firefox

### Recording Playback

Record Mode	General; alarm; motion detection; intelligent; POS
Recording Playback	1/4
Backup Method	USB device and network

Playback Mode	Instant playback; general playback; event playback; tag playback; smart playback
<b>Alarm</b>	
General Alarm	Motion detection; alarm box; HDCVI alarm; camera external alarm; network alarm; PIR alarm
Anomaly Alarm	Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline
Intelligent Alarm	Face detection; face recognition; perimeter protection; SMD Plus
Alarm Linkage	Record; snapshot (panoramic); IPC external alarm output; audio; buzzer; log; preset; email
<b>Ports</b>	
Audio Input	1-channel RCA 4-channel BNC (Coaxial Audio)
Audio Output	1-channel RCA
Two-way Talk	Yes (share the same audio input with the first channel)
Disk Interface	1 SATA port, up to 16 TB. This limit varies depending on the environment temperature.
RS-485	1
USB	2 (1 front USB 2.0 port, 1 rear USB 2.0 port)
HDMI	1
VGA	1
Network Port	1 (10/100 Mbps Ethernet port, RJ-45)
<b>General</b>	
Power Supply	12 VDC, 1.5A
Power Consumption	<5 W(without HDD)
Net Weight	0.84 kg (1.85 lb)
Gross Weight	1.37 kg (3.02 lb)
Product Dimensions	260.0 mm × 237.8 mm × 47.6 mm (10.24" × 9.36" × 1.87") (W × D × H)
Packaging Dimensions	333.0 mm × 89.0 mm × 315.0 mm (13.11" × 3.50" × 12.40") (W × D × H)
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)
Operating Humidity	10%–90% (RH), non-condensing
Installation	Desktop
Certifications	CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014

### Accessories

Optional:



DHI-SSD-V800S256G  
SSD



DHI-SSD-V800S512G  
SSD




DHI-SSD-V800S1TB  
SSD



DHI-ARB1606  
Alarm Box


### Dimensions (mm[inch])



### Ordering Information

Type	Model	Description
DIGITAL VIDEO RECORDER	DH-XVR5104HS-I3	4CH Penta-brid 5MP Value/1080P Compact 1U 1HDD WizSense Digital Video Recorder

Panels



- |               |                             |
|---------------|-----------------------------|
| 1 VIDEO IN    | 2 AUDIO IN, RCA Connector   |
| 3 VGA Port    | 4 Ground                    |
| 5 Power Input | 6 USB Port                  |
| 7 RS-485 Port | 8 Network Port              |
| 9 HDMI Port   | 10 AUDIO OUT, RCA Connector |